


6 SERIES

**Product Description & Features**

- Low profile
- Interior or exterior doors
- Doors may be single or double acting
- Non-handed
- Recommended for moderate traffic, medium weight doors
- Low profile concealed channel designed for installation in aluminum storefront doors
- Heavy shock absorber spring provides 5-7° compression before dead stop
- Complete screw kit allows for installation in wood or metal door and frame
- For security areas, Torx® screws optional
- Standard architectural finishes
- Durable slider cam
- 110° maximum opening
- 1-3/4" minimum door thickness
- Channel is 1-1/4" wide by 1/2" deep
- UL listed for fire door assemblies
- Hanging means other than standard butts or offset pivots require special templating and pricing. Consult factory
- Available in stop function only



**Chart (in inches)**

Butts Offset Pivots	Center Hung Pivots	Model Number
<b>Door Opening</b>		<b>Stop</b>
*24 - 28	—	6-136
28-1/16 - 33	30 - 36	6-236
33-1/16 - 38	36-1/16 - 41	6-336
38-1/16 - 43	41-1/16 - 46	6-436
43-1/16 - 48	46-1/16 - 50	6-536

<b>ANSI No.</b>	
Shipping Weight 4.5 lbs.	<b>Stop</b> C01541

**\*Butt hung only on this size door. No swing clear hinges.**