



NEW

COLOR SELECTABLE SECURITY LIGHTING



FIG. 1



LAMPS ONLY
NO MOTION SENSOR

FIG. 2



MOTION SENSOR MODES: AUTO MODE,
DUSK TO DAWN MODE, MANUAL OVER-
RIDE MODE, TEST MODE

- 2.5kV Surge Protection
- Easy Install: Crossbar Installation
- Die-Cast Aluminum Housing with Tempered Glass Lens

HIGHER LUMENS PER WATT THAN PREVIOUS MODELS
INCREASED BEAM ANGLE
TRIAC DIMMING

CAT. NO.	FIG.	DESCRIPTION	MOTION ACTIVATED	HOUSING COLOR	COLOR TEMP	WATTS	VOLTS	LUMENS	CASE QTY
72580B	1	ROUND 2 HEAD	NO	BRONZE	3000K 4000K 5000K	24W	120V	2,500	12
72581B	1	ROUND 2 HEAD	NO	WHITE	3000K 4000K 5000K	24W	120V	2,500	12
72568B	2	ROUND 2 HEAD	YES	BRONZE	3000K 4000K 5000K	24W	120V	2,500	12
72563B	2	ROUND 2 HEAD	YES	WHITE	3000K 4000K 5000K	24W	120V	2,500	12

NEW

MOTION SENSOR ONLY



- Motion Sensor Modes: Auto Mode, Dusk to Dawn Mode, Manual Override Mode, Test Mode
- Detection Range: Max 180°
- Detection Distance: 5' - 60' (adjustable)
- Time Setting: 10sec. - 10min.
- Input Power: 120 VAC, 60Hz
- Load Rating: Max. 500W Incandescent lamp or Max 200W LED Driver/LED Bulb
- Operation LUX: ON to OFF Max: 800LUX
OFF to ON 20-90LUX
- Power Consumption: Max 0.5 Watts on stand-by
- Operation Temperature: -22°F to 122°F
- Polycarbonate Enclosure
- Used With Morris Items: 72580B, 72581B

CAT. NO.	DETECTION ANGLE	HOUSING COLOR	CASE QTY
72582B	180°	BRONZE	48
72583B	180°	WHITE	48

PLEASE REVIEW ONLINE SPECIFICATION SHEETS. IMAGES AND CERTIFICATIONS MAY NOT BE 100% REPRESENTATIVE OF ALL PRODUCTS LISTED. TO VIEW DETAILS OF OUR DLC QUALIFIED PRODUCTS, PLEASE CONSULT THE DLC QUALIFIED PRODUCTS LIST AT WWW.DESIGNLIGHTS.ORG/QPL

WWW.MORRISPRODUCTS.COM

1-888-777-6678