



PROGRAM LOCK PIN:
 MUST BE PROGRAMMED TO
 MUST PROGRAM HIGH/LOW OUTPUT FOR "ON DOOR OPEN" TO LOW.
 UTC/CASI MICRO/PX-2000 SUPPORTS UP TO 4 AD LOCKS VIA WIU-2 (WIEGAND INTERFACE UNIT). WIU-2 SUPPORTS A SINGLE AD LOCK. WIU-2 IS MOUNTED IN A SINGLE GANG
 ELECTRICAL BOX BETWEEN THE MICRO/PX-2000 AND THE PIM400-TD2 X RLB D. ONLY ONE AD400 SHOWN ON THIS DIAGRAM FOR CLARITY.
 WIRING SHOWN REFLECTS WIRING FROM UTC/CASI MICRO/PX-2000 TO WIU-2 TO PIM ONLY. ADDITIONAL WIRING WILL BE REQUIRED AND IS NOT SHOWN HERE.
 UL294 POWER SUPPLIES SHOULD NOT BOND EARTH GROUND TO SIGNAL GROUND
 RTE AND TROUBLE MONITORING NOT DONE IN THIS CONFIGURATION.

CREATOR: BRENDIA DOVE 07/02/12
 APPROVED: ALEX SZABO

TITLE: UTC/CASI MICRO/PX-2000 X WIU-2 WITH
 PIM400-TD2 X RLB D /AD400

621121UTC-CASI
 Rev 2
 rev 2-1-15-12