

ENVIRONMENTAL PRODUCT DECLARATION

SARGENT

10 LINE CYLINDRICAL LOCK



The SARGENT 10 Line Cylindrical Lock, is an ANSI/BHMA A156.2 Series 4000 Grade 1 mechanical cylindrical lock. It has a reversible stainless steel latch with deadlatch.

SARGENT **ASSA ABLOY**

ASSA ABLOY is committed to providing products and services that are environmentally sound throughout the entire production process and the product lifecycle. Our unconditional aim is to make sustainability a central part of our business philosophy and culture, but even more important is the job of integrating sustainability into our business strategy. The employment of EPDs will help architects, designers and LEED-APs select environmentally preferable door openings. The SARGENT 10 Line Cylindrical Lock EPD provides detailed requirements with which to evaluate the environmental and human health impacts related to producing our door openings. ASSA ABLOY will continue our efforts to protect the environment and health of our customers/end users and will utilize the EPD as one means to document those efforts.



ENVIRONMENTAL PRODUCT DECLARATION

SARGENT

ASSA ABLOY

SARGENT Manufacturing Company
10 Line Cylindrical Lock

According to EN 15804 and ISO 14025

Dual Recognition by UL Environment and Institut Bauen und Umwelt e.V.


This declaration is an environmental product declaration (EPD) in accordance with ISO 14025. EPDs rely on Life Cycle Assessment (LCA) to provide information on a number of environmental impacts of products over their life cycle. **Exclusions:** EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc. **Accuracy of Results:** EPDs regularly rely on estimations of impacts, and the level of accuracy in estimation of effect differs for any particular product line and reported impact. **Comparability:** EPDs are not comparative assertions and are either not comparable or have limited comparability when they cover different life cycle stages, are based on different product category rules or are missing relevant environmental impacts. EPDs from different programs may not be comparable.



| | |
|------------------------|--|
| PROGRAM OPERATOR | UL Environment |
| DECLARATION HOLDER | ASSA ABLOY / SARGENT Manufacturing Company |
| ULE DECLARATION NUMBER | 4786545067.129.1 |
| IBU DECLARATION NUMBER | EPD-ASA-20150146-IBA1-EN |
| DECLARED PRODUCT | 10 Line Cylindrical Lock |
| REFERENCE PCR | IBU: PCR Locks and fittings (mechanical & electromechanical locks & fittings), 07-2014 |

| | |
|--------------------|--------------|
| DATE OF ISSUE | May 18, 2015 |
| PERIOD OF VALIDITY | 5 years |

| | |
|-----------------------------|---|
| CONTENTS OF THE DECLARATION | General information Product / Product description LCA calculation rules LCA scenarios and further technical information LCA results References |
|-----------------------------|---|

| | |
|---|---|
| The PCR review was conducted by: | IBU – Institut Bauen und Umwelt e.V. PCR was approved by the Independent Expert Committee (SVA) |
| The CEN Norm EN 15804 serves as the core PCR. This declaration was independently verified in accordance with ISO 14025 by Underwriters Laboratories <input type="checkbox"/> INTERNAL <input checked="" type="checkbox"/> EXTERNAL |  Wade Stout |
| This life cycle assessment was independently verified in accordance with EN 15804 and the reference PCR by: | IBU – Institut Bauen und Umwelt e.V. |



1. General Information

SARGENT Manufacturing Company

Programme holder

IBU - Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Declaration number

EPD-ASA-20150146-IBA1-EN

This Declaration is based on the Product Category Rules:

IBU: PCR Locks and fittings: (mechanical & electromechanical locks & fittings), 07-2014 (PCR tested and approved by the independent expert committee)

Issue date

18.05.2015

Valid to

17.05.2020



Prof. Dr.-Ing. Horst J. Bossenmayer
(President of Institut Bauen und Umwelt e.V.)



Dr.-Ing. Burkhard Lehmann
(Managing Director IBU)

10 Line Cylindrical Lock

Owner of the Declaration

SARGENT Manufacturing Company
100 Sargent Drive,
New Haven, CT 06511 USA

Declared product / Declared unit

The declaration represents 1 single point lock consisting of the following :

- 10 Line Cylindrical Lock inclusive of lock body, latches, levers, roses, strikes and all mounting hardware.

Scope:


This EPD is based on the full lifecycle of 1 SARGENT 10 Line Cylindrical Lock. Data was collected from the lock case manufacturer in New Haven, Connecticut (US). The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Verification

The CEN Standard EN 15804 serves as the core PCR

Independent verification of the declaration and data according to ISO 14025

- internally externally



Dr. Wolfram Trinius
(Independent verifier appointed by SVA)

2. Product

2.1 Product description

The SARGENT 10 Line Cylindrical Lock, is an ANSI/BHMA A156.2 Series 4000 Grade 1 mechanical cylindrical lock. It has a reversible stainless steel latch with deadlatch.

The 10 Line is available with 21 different mechanical locking functions 2 electrical functions, 11 Architectural grade finishes and an array of lever options.

- ANSI/BHMA A156.2 Series 4000 Grade 1 Certified
- Meets A117.1 Accessibility Code

2.2 Application

The locks are designed for single or double leaf doors with mullions. The locks are typically installed in commercial buildings, such as

- Commercial campuses
- Colleges
- Detention centers

- Dormitories
- Hospitals
- Warehouses
- Psychiatric wards
- Any high abuse applications

2.3 Technical Data

The following table lists the technical properties of SARGENT 10 Line Cylindrical Lock:

Technical data

| Item | Value |
|----------------|--|
| Backset | 2-3/4" (70mm) Standard 2-3/8" (60MM), 3-3/4" (95mm), 5" (127mm) Optional |
| Door Thickness | 1-3/4" (44mm) thick standard adjust to 2" (51mm) |
| Door prep | 161 Door Prep Modified |
| Handing | Non Handed |
| Keying | Can be masterkeyed or grand masterkeyed. |

2.4 Placing on the market / Application rules

The products are subject to UL marking. Relevant norms are: ANSI/BHMA A156.2 American Standard for Bored & Preassembled Locks and Latches.

2.5 Delivery status

Delivered as a complete unit, inclusive of lockbody, trim, strike and fasteners or as separate lock case. Delivered in a box size 8.25" x 7" x 4" (210 x 178 x 102mm).

2.6 Base materials / Ancillary materials

The average composition of the SARGENT 10 Line Cylindrical lock is as following:

| Component | Percentage in mass (%) |
|-----------------|------------------------|
| Brass | 15.8 |
| Zinc | 36.4 |
| Steel | 44.9 |
| Stainless steel | 2.2 |
| Plastic | 0.4 |
| Other | 0.3 |
| Total | 100.0 |

2.7 Manufacture

Products are manufactured and assembled in the United States and are supported by tier-1 supplier in Mexico. The components come from processes such as stamped steel, zinc and steel casting.

2.8 Environment and health during manufacturing

ASSA ABLOY is committed to integrating our sustainability efforts across the organization. Our priorities are to: reduce resource and energy consumption; reduce carbon emissions; improve water and waste management; improve health and safety performance in operations; improve sustainability performance within our supply chain and enhance the sustainability performance in ASSA ABLOY's supply of door opening solutions. Inspections, audits, and reviews are conducted periodically to ensure that applicable standards are met and environmental management systems are evaluated.

Our Code of Conduct covers business ethics, workers' rights, human rights, environment and health & safety, consumer interests and community outreach. It provides the framework for ASSA ABLOY's daily operations.

- Sargent Manufacturing is in the process of certification of both ISO 9001:2008 and ISO 14001:2004, expected certification date 1/2015
- Any waste metals during machining are separated and recycled. The waste water is delivered to waste treatment plant.

2.9 Product processing/Installation

SARGENT 10 Line Cylindrical locks are distributed through, and installed by trained technicians, such as locksmiths or security technicians. Preparation of doors and frames are conducted at the door manufacturer's production site.

2.10 Packaging

All packaging is fully recyclable. The packaging material is composed by cardboard (app. 70%) and plastic foil (app. 30%).

| Material | Value (%) |
|-----------------|--------------|
| Cardboard/paper | 98.4 |
| Plastic | 1.6 |
| Total | 100.0 |

2.11 Condition of use

Locks require no maintenance.

2.12 Environment and health during use

There is no harmful emissive potential. No damage to health or impairment is expected under normal use corresponding to the intended use of the product.

2.13 Reference service life

The reference service life of 30 years is based on a typical installation of a SARGENT 10 Line Cylindrical lock as a security lock operated when the facilities are to be closed or opened. If operations per day exceeds that typical wear the locks are exposed to the life time is limited to 800,000 cycles in accordance with ANSI/BHMA A156.2.

Influences on ageing when applied in accordance with the rules of technology.

2.14 Extraordinary effects

Fire

Suitable for use in fire and smoke doors: (listed by Underwriters Laboratories).

Water

Contain no substances that have any impact on water in case of flood. Electric operation of the device will be influenced negative.

Mechanical destruction

No danger to the environment can be anticipated during mechanical destruction.

2.15 Re-use phase

The product is possible to re-use during the reference service life and be moved to one door to another. The lock can either be sent back to SARGENT for recycling or to a professional recycling service provider. The majority, by weight, of components are zinc, brass steel, and stainless steel, which can be recycled. The plastic components can be used for energy recovery in an incineration process.

2.16 Disposal

The product can be mechanically dissembled to separate the different materials. 99.76% of the materials used are recyclable. The rest is disposed as a construction waste for landfill.

2.17 Further information

SARGENT Manufacturing Company
100 Sargent Drive,
New Haven, CT 06511 USA
Tel 800-727-5477
www.sargentlock.com

3. LCA: Calculation rules

3.1 Declared Unit

The declaration refers to the functional unit of 1 piece of single point lock SARGENT 10 Line Cylindrical lock as specified in Part B requirements on the EPD for PCR Locks and fittings: (mechanical & electromechanical locks & fittings).

Declared unit

| Name | Value | Unit |
|---------------------------|-------|----------------------------|
| Declared unit | 1 | Piece of single point lock |
| Mass | 1.81 | kg |
| Conversion factor to 1 kg | 0.535 | - |

3.2 System boundary

Type of the EPD: cradle to gate - with Options
The following life cycle phases were considered:

Production stage:

- A1 – Raw material extraction and processing
- A2 – Transport to the manufacturer and
- A3 – Manufacturing

Construction stage:

- A4 - Transport from the gate to the site
- A5 – Packaging waste processing

The use stage:

- B2 - Maintenance (cleaning of the locks)

End-of-life stage:

- C2 – Transport to waste processing
- C4 – Disposal (landfill)

This includes provision of all materials, products and energy, packaging processing and its transport, as well as waste processing up to the end-of waste state or disposal of final residues.

- D - Declaration of all benefits or recycling potential from EOL and A5.

3.3 Estimates and assumptions

EoL:

In the End-of-Life phase, for all the materials which can be recycled, a recycling scenario with 100% collection rate was assumed.

3.4 Cut-off criteria

In the assessment, all available data from the production process are considered, i.e. all raw materials used, auxiliary materials (e.g. lubricants), thermal energy consumption and electric power consumption - including material and energy flows contributing less than 1% of mass or energy (if available). In case a specific flow contributing less than 1% in mass or energy is not available, worst case assumption proxies are selected to represent the respective environmental impacts.

Impacts relating to the production of machines and facilities required during production are out of the scope of this assessment.

3.5 Background data

For life cycle modeling of the considered products, the GaBi 6 Software System for Life Cycle Engineering, developed by PE INTERNATIONAL AG, is used /GaBi 6 2013/. The GaBi-database contains consistent and documented datasets which are documented in the online GaBi-documentation /GaBi 6 2013D/.

To ensure comparability of results in the LCA, the basic data of GaBi database were used for energy, transportation and auxiliary materials.

3.6 Data quality

The requirements for data quality and background data correspond to the specifications of the /IBU PCR PART A/.

PE INTERNATIONAL performed a variety of tests and checks during the entire project to ensure high quality of the completed project. This obviously includes an extensive review of project-specific LCA models as well as the background data used.

The technological background of the collected data reflects the physical reality of the declared products. The datasets are complete and conform to the system boundaries and the criteria for the exclusion of inputs and outputs.

All relevant background datasets are taken from the GaBi 6 software database. The last revision of the used background data has taken place not longer than 10 years ago.

3.7 Period under review

The period under review is 2013/14 (12 month average).

3.8 Allocation

Regarding incineration, the software model for the waste incineration plant (WIP) is adapted according to the material composition and heating value of the combusted material. In this EPD, the following specific life cycle inventories for the WIP are considered for:

- Waste incineration of plastic
- Waste incineration of paper

Regarding the recycling material of metals, the metal parts in the EoL are declared as end-of-waste status. Thus, these materials are considered in module D. Specific information on allocation within the background data is given in the GaBi dataset documentation.

3.9 Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

4. LCA: Scenarios and additional technical information

The following technical information is a basis for the declared modules or can be used for developing specific scenarios in the context of a building assessment if modules are not declared (MND).

Installation into the building (A5)

| Name | Value | Unit |
|---|-------|------|
| Output substances following waste treatment on site (Paper packaging) | 0.055 | kg |
| Output substances following waste treatment on site (Plastic packaging) | 0.001 | kg |

Maintenance (B2)

| Name | Value | Unit |
|------------------------------|-------|------|
| Other resources – detergents | 0.1 | kg/a |
| Water for cleaning | 0.1 | kg/a |

Reference service life

| Name | Value | Unit |
|------------------------|-------|------|
| Reference service life | 30 | a |

End of life (C1-C4)

| Name | Value | Unit |
|--|-------|------|
| Collected separately Brass, stainless steel, steel. zinc, plastics | 1.81 | kg |
| Collected as mixed construction waste – construction waste for landfilling | 0.005 | kg |
| Reuse Plastics | 0.01 | kg |
| Recycling Brass, stainless steel, steel. zinc | 1.8 | kg |
| Landfilling - Construction waste for landfilling | 0.005 | kg |

Reuse, recovery and/or recycling potentials (D), relevant scenario information

| Name | Value | Unit |
|--|-------|------|
| Collected separately waste type Cylindrical lock (including packaging) | 1.87 | kg |
| Recycling Brass | 15.32 | % |
| Recycling Steel | 43.6 | % |
| Recycling Stainless steel | 2.17 | % |
| Recycling Zinc | 35.31 | % |
| Reuse Plastics | 0.37 | % |
| Reuse Paper packaging (from A5) | 2.94 | % |
| Reuse Plastic packaging (from A5) | 0.05 | % |
| Loss Construction waste for landfilling (no recycling potential) | 0.24 | % |

5. LCA: Results

Results shown below were calculated using CML 2001 – Apr. 2013 Methodology.

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

| PRODUCT STAGE | | | CONSTRUCTION PROCESS STAGE | | USE STAGE | | | | | | | END OF LIFE STAGE | | | | BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES |
|---------------------|-----------|---------------|-------------------------------------|----------|-----------|-------------|--------|---------------------------|-----------------------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|---|
| Raw material supply | Transport | Manufacturing | Transport from the gate to the site | Assembly | Use | Maintenance | Repair | Replacement ¹⁾ | Refurbishment ¹⁾ | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery-Recycling-potential |
| A1 | A2 | A3 | A4 | A5 | B1 | B2 | B3 | B4 | B5 | B6 | B7 | C1 | C2 | C3 | C4 | D |
| X | X | X | X | X | MND | X | MND | MND | MND | MND | MND | MND | X | MND | X | X |

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: One piece of single point lock SARGENT 10 Line Cylindrical lock

| Parameter | Parameter | Unit | A1 - A3 | A4 | A5 | B2 | C2 | C4 | D |
|-----------|--|--|----------|-----------|----------|-----------|-----------|----------|-----------|
| GWP | Global warming potential | [kg CO ₂ -Eq.] | 2.89E+01 | 5.53E-02 | 8.91E-02 | -2.31E+00 | 4.64E-02 | 1.25E-02 | -2.79E+00 |
| ODP | Depletion potential of the stratospheric ozone layer | [kg CFC11-Eq.] | 6.91E-09 | 1.64E-12 | 4.04E-13 | 6.71E-11 | 1.60E-12 | 3.75E-14 | -6.99E-10 |
| AP | Acidification potential of land and water | [kg SO ₂ -Eq.] | 9.10E-02 | 2.54E-04 | 2.04E-05 | 4.80E-02 | 2.13E-04 | 3.18E-06 | -1.36E-02 |
| EP | Eutrophication potential | [kg (PO ₄) ³⁻ -Eq.] | 5.82E-03 | 5.62E-05 | 3.50E-06 | 2.85E-02 | 4.70E-05 | 2.40E-07 | -7.58E-04 |
| POCP | Formation potential of tropospheric ozone photochemical oxidants | [kg Ethen Eq.] | 6.22E-03 | -7.79E-05 | 1.43E-06 | 9.33E-04 | -6.48E-05 | 1.54E-07 | -8.82E-04 |
| ADPE | Abiotic depletion potential for non fossil resources | [kg Sb Eq.] | 4.81E-03 | 2.31E-09 | 1.72E-09 | 9.32E-07 | 1.97E-09 | 8.23E-10 | -3.92E-03 |
| ADPF | Abiotic depletion potential for fossil resources | [MJ] | 3.47E+02 | 7.65E-01 | 2.53E-02 | 5.86E+01 | 6.42E-01 | 5.27E-03 | -3.42E+01 |

RESULTS OF THE LCA - RESOURCE USE: One piece of single point lock SARGENT 10 Line Cylindrical lock

| Parameter | Parameter | Unit | A1 - A3 | A4 | A5 | B2 | C2 | C4 | D |
|-----------|--|-------------------|----------|----------|----------|----------|----------|----------|-----------|
| PERE | Renewable primary energy as energy carrier | [MJ] | 3.95E+01 | - | - | - | - | - | - |
| PERM | Renewable primary energy resources as material utilization | [MJ] | 0.00E+00 | - | - | - | - | - | - |
| PERT | Total use of renewable primary energy resources | [MJ] | 3.95E+01 | 3.58E-02 | 2.34E-03 | 1.18E+02 | 3.10E-02 | 3.86E-04 | -1.18E+01 |
| PENRE | Non renewable primary energy as energy carrier | [MJ] | 4.19E+02 | - | - | - | - | - | - |
| PENRM | Non renewable primary energy as material utilization | [MJ] | 0.00E+00 | - | - | - | - | - | - |
| PENRT | Total use of non renewable primary energy resources | [MJ] | 4.19E+02 | 7.80E-01 | 2.96E-02 | 6.21E+01 | 6.58E-01 | 5.86E-03 | -4.58E+01 |
| SM | Use of secondary material | [kg] | 1.53E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| RSF | Use of renewable secondary fuels | [MJ] | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| NRSF | Use of non renewable secondary fuels | [MJ] | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| FW | Use of net fresh water | [m ³] | 1.54E-01 | 3.68E-05 | 2.58E-04 | 6.13E-02 | 3.34E-05 | 3.04E-05 | -4.33E-02 |

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES: One piece of single point lock SARGENT 10 Line Cylindrical lock

| Parameter | Parameter | Unit | A1 - A3 | A4 | A5 | B2 | C2 | C4 | D |
|-----------|-------------------------------|------|----------|----------|----------|----------|----------|----------|-----------|
| HWD | Hazardous waste disposed | [kg] | 1.10E-02 | 6.68E-06 | 2.04E-06 | 3.63E-03 | 6.40E-06 | 4.09E-07 | -4.78E-03 |
| NHWD | Non hazardous waste disposed | [kg] | 7.41E-01 | 1.05E-04 | 2.39E-03 | 3.56E-01 | 8.98E-05 | 1.16E-03 | 3.27E-02 |
| RWD | Radioactive waste disposed | [kg] | 2.83E-02 | 6.15E-06 | 1.71E-06 | 1.38E-03 | 5.99E-06 | 2.33E-07 | -4.65E-03 |
| CRU | Components for re-use | [kg] | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | - |
| MFR | Materials for recycling | [kg] | 0.00E+00 | 0.00E+00 | 5.49E-02 | 0.00E+00 | 0.00E+00 | 0.00E+00 | - |
| MER | Materials for energy recovery | [kg] | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | - |
| EEE | Exported electrical energy | [MJ] | 0.00E+00 | 0.00E+00 | 1.14E-01 | 0.00E+00 | 0.00E+00 | 2.38E-02 | - |
| EET | Exported thermal energy | [MJ] | 0.00E+00 | 0.00E+00 | 3.22E-01 | 0.00E+00 | 0.00E+00 | 6.54E-02 | - |

6. LCA: Interpretation

This chapter contains an interpretation of the Life Cycle Impact Assessment categories. Stated percentages in the whole interpretation are related to the overall life cycle, excluding credits (module D).

The production phase (modules A1-A3) contributes between 65% and 99% to the overall results for all the environmental impact assessment categories hereby considered, except for the eutrophication potential (EP), for which the contribution from the production phase accounts for app. 16%.

Within the production phase, the main contribution for all the impact categories is the production of steel and mainly due to the energy consumption on this process. Steel and zinc account in total with app. 82% to the overall mass of the product, therefore, the impacts are in line with the mass composition of the product. The

environmental impacts for the transport (A2) have a negligible impact within this stage. Relatively high impact on EP (83%) during the maintenance phase (module B2) is a result of generated waste water during maintenance of the product. Eutrophication is the enrichment of nutrients in a certain place and it can be aquatic or terrestrial. Waste water contributes to eutrophication therefore, as expected, it is mainly related with the maintenance of the product (B2).

In the end-of-life phase, there are loads and benefits (module D, negative values) considered. The benefits are considered beyond the system boundaries and are declared for the recycling potential of the metals and for the credits from the incineration process (energy substitution).

7. Requisite evidence

Not applicable in this EPD.

8. References

Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin (pub.):
Generation of Environmental Product Declarations (EPDs);

General principles

for the EPD range of Institut Bauen und Umwelt e.V. (IBU), 2013-04
www.bau-umwelt.de

IBU PCR Part A

IBU PCR Part A: Institut Bauen und Umwelt e.V., Berlin (pub.): Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report. April 2013
www.bau-umwelt.de

IBU PCR Part B

IBU PCR Part B: PCR Guidance-Texts for Building-Related Products and Services. From the range of Environmental Product Declarations of Institute Construction and Environment e.V. (IBU). Part B: Requirements on the EPD for Locks and fittings.
www.bau-umwelt.com

ANSI/A117.1

ANSI/A117.1: Accessible and Usable Buildings and Facilities

ANSI/BHMA A156.13

ANSI/BHMA A156.13: Mortise Locks

ISO 14001

ISO 14001: Environmental management systems - Requirements with guidance for use (ISO 14001:2004 + Cor. 1:2009)

ISO 14025

ISO 14025:2011-10: Environmental labels and declarations — Type III environmental declarations — Principles and procedures

EN 15804

EN 15804: 2012+A1:2014: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

GaBi 6 2013

GaBi 6 2013: Software-System and Database for Life Cycle Engineering. Copyright, TM. Stuttgart, Echterdingen, 1992-2013.

GaBi 6 2013D

GaBi 6 2013D: Documentation of GaBi 6: Software-System and Database for Life Cycle Engineering. Copyright, TM. Stuttgart, Echterdingen, 1992-2013.
<http://documentation.gabi-software.com/>

UBC 7-2 (1997)

UBC 7-2 (1997): Uniform Building Code, Volume 2

SARGENT

ASSA ABLOY

UL and ULc Standards

ULC Standards develops and publishes standards and specifications for products having a bearing on fire, life safety and security, crime prevention, energy efficiency, environmental safety, security of assets and facilities, live working and workplace safety and other areas. ULC Standards is accredited by the Standards Council of Canada as a consensus based Standards Development Organization under the National Standards System of Canada.

9. Annex

Results shown below were calculated using TRACI Methodology.

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

| PRODUCT STAGE | | | CONSTRUCTION PROCESS STAGE | | USE STAGE | | | | | | | END OF LIFE STAGE | | | | BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES |
|---------------------|-----------|---------------|-------------------------------------|----------|-----------|-------------|--------|---------------------------|-----------------------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|---|
| Raw material supply | Transport | Manufacturing | Transport from the gate to the site | Assembly | Use | Maintenance | Repair | Replacement ¹⁾ | Refurbishment ¹⁾ | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery-Recycling-potential |
| A1 | A2 | A3 | A4 | A5 | B1 | B2 | B3 | B4 | B5 | B6 | B7 | C1 | C2 | C3 | C4 | D |
| X | X | X | X | X | MND | X | MND | MND | MND | MND | MND | MND | X | MND | X | X |

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: One piece of single point lock SARGENT 10 Line Cylindrical lock

| Parameter | Parameter | Unit | A1 - A3 | A4 | A5 | B2 | C2 | C3 | C4 | D |
|-----------|--|---------------------------|----------|----------|----------|-----------|----------|----------|-----------|----------|
| GWP | Global warming potential | [kg CO ₂ -Eq.] | 2.89E+01 | 5.53E-02 | 8.91E-02 | -2.31E+00 | 4.64E-02 | 1.25E-02 | -2.79E+00 | 2.89E+01 |
| ODP | Depletion potential of the stratospheric ozone layer | [kg CFC11-Eq.] | 7.35E-09 | 1.74E-12 | 4.30E-13 | 7.13E-11 | 1.70E-12 | 3.99E-14 | -7.43E-10 | 7.35E-09 |
| AP | Acidification potential of land and water | [kg SO ₂ -Eq.] | 8.68E-02 | 3.28E-04 | 2.47E-05 | 5.62E-02 | 2.75E-04 | 3.72E-06 | -1.28E-02 | 8.68E-02 |
| EP | Eutrophication potential | [kg N-eq.] | 4.39E-03 | 2.29E-05 | 1.40E-06 | 4.43E-02 | 1.92E-05 | 1.13E-07 | -4.56E-04 | 4.39E-03 |
| Smog | Ground-level smog formation potential | [kg O ₃ -eq.] | 8.58E-01 | 6.64E-03 | 5.65E-04 | 2.31E-01 | 5.55E-03 | 2.92E-05 | -1.14E-01 | 8.58E-01 |
| Resources | | [MJ] | 2.97E+01 | 1.08E-01 | 2.95E-03 | 7.63E+00 | 9.07E-02 | 5.42E-04 | -3.13E+00 | 2.97E+01 |

RESULTS OF THE LCA - RESOURCE USE: One piece of single point lock SARGENT 10 Line Cylindrical lock

| Parameter | Parameter | Unit | A1 - A3 | A4 | A5 | B2 | C2 | C4 | D |
|-----------|--|-------------------|----------|----------|----------|----------|----------|----------|-----------|
| PERE | Renewable primary energy as energy carrier | [MJ] | 3.95E+01 | - | - | - | - | - | - |
| PERM | Renewable primary energy resources as material utilization | [MJ] | 0.00E+00 | - | - | - | - | - | - |
| PERT | Total use of renewable primary energy resources | [MJ] | 3.95E+01 | 3.58E-02 | 2.34E-03 | 1.18E+02 | 3.10E-02 | 3.86E-04 | -1.18E+01 |
| PENRE | Non renewable primary energy as energy carrier | [MJ] | 4.19E+02 | - | - | - | - | - | - |
| PENRM | Non renewable primary energy as material utilization | [MJ] | 0.00E+00 | - | - | - | - | - | - |
| PENRT | Total use of non renewable primary energy resources | [MJ] | 4.19E+02 | 7.80E-01 | 2.96E-02 | 6.21E+01 | 6.58E-01 | 5.86E-03 | -4.58E+01 |
| SM | Use of secondary material | [kg] | 1.53E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| RSF | Use of renewable secondary fuels | [MJ] | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| NRSF | Use of non renewable secondary fuels | [MJ] | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| FW | Use of net fresh water | [m ³] | 1.54E-01 | 3.68E-05 | 2.58E-04 | 6.13E-02 | 3.34E-05 | 3.04E-05 | -4.33E-02 |

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

One piece of single point lock SARGENT 10 Line Cylindrical lock

| Parameter | Parameter | Unit | A1 - A3 | A4 | A5 | B2 | C2 | C4 | D |
|-----------|-------------------------------|------|----------|----------|----------|----------|----------|----------|-----------|
| HWD | Hazardous waste disposed | [kg] | 1.10E-02 | 6.68E-06 | 2.04E-06 | 3.63E-03 | 6.40E-06 | 4.09E-07 | -4.78E-03 |
| NHWD | Non hazardous waste disposed | [kg] | 7.41E-01 | 1.05E-04 | 2.39E-03 | 3.56E-01 | 8.98E-05 | 1.16E-03 | 3.27E-02 |
| RWD | Radioactive waste disposed | [kg] | 2.83E-02 | 6.15E-06 | 1.71E-06 | 1.38E-03 | 5.99E-06 | 2.33E-07 | -4.65E-03 |
| CRU | Components for re-use | [kg] | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | - |
| MFR | Materials for recycling | [kg] | 0.00E+00 | 0.00E+00 | 5.49E-02 | 0.00E+00 | 0.00E+00 | 0.00E+00 | - |
| MER | Materials for energy recovery | [kg] | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | - |
| EEE | Exported electrical energy | [MJ] | 0.00E+00 | 0.00E+00 | 1.14E-01 | 0.00E+00 | 0.00E+00 | 2.38E-02 | - |
| EET | Exported thermal energy | [MJ] | 0.00E+00 | 0.00E+00 | 3.22E-01 | 0.00E+00 | 0.00E+00 | 6.54E-02 | - |

**Publisher**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 3087748-0
Fax +49 (0)30 3087748-29
Mail info@bau-umwelt.com
Web www.bau-umwelt.com

**Programme holder**

Institut Bauen und Umwelt e.V.
Panoramastr 1
10178 Berlin
Germany

Tel +49 (0)30 3087748-0
Fax +49 (0)30 3087748-29
Mail info@bau-umwelt.com
Web www.bau-umwelt.com

**Author of the Life Cycle Assessment**

PE INTERNATIONAL AG
Hauptstraße 111-113
70771 Leinfelden-Echterdingen
Germany

Tel +49 (0)711 341817-0
Fax +49 (0)711 341817-25
Mail info@pe-international.com
Web www.pe-international.com

**Owner of the Declaration**

SARGENT Manufacturing Company
100 Sargent Drive,
New Haven, CT 06511 USA

Tel 800-727-5477
Web www.sargentlock.com
www.assaabloydss.com